
# TOPPERFO® type 20/20/6 M




### Panels


Panels are used for removable or fixed ceilings and walls and will have visible reveal joints. Panels can be provided with a number of different edge conditions and are also suited for cabinet fronts and room dividers. They can be provided with the unperforated border of your specification.

Class C Fire Rated			Class A Fire Rated				
Paint	Wood Veneer	Melamine	Paint	Wood Veneer	Melamine		
16 mm (0.63")	17 mm (0.67")	16 mm (0.63")	16 mm (0.63")	17 mm (0.67")	16 mm (0.63")		
max.							
3648 x 1216	3648 x 1216	3648 x 1216	3648 x 1216	3648 x 1216	3648 x 1216		
(143.63" x 47.8")	(143.63" x 47.8")	(143.63" x 47.8")	(143.63" x 47.8")	(143.63" x 47.8")	(143.63" x 47.8")		
ideal = means optimal use of MDF core - custom lengths/widths are always available							
2032 x 992	2032 x 992	2032 x 992	2032 x 992	2032 x 992	2032 x 992		
(80" x 39")	(80" x 39")	(80" x 39")	(80" x 39")	(80" x 39")	(80" x 39")		
2780 x 992	2780 x 992	2780 x 992	2780 x 992	2780 x 992	2780 x 992		
(109.45 x 39")	(109.45 x 39")	(109.45 x 39")	(109.45" x 39")	(109.45 x 39")	(109.45" x 39")		
3648 x 640 (143.63" x 25.2")	3648 x 640 (143.63" x 25.2")			3648 x 640 (143.63" x 25.2")			

#### Finishing Options












EDGE BANDED WITH CLEAR UNPERFORATED BORDERS - AS SPECIFIED

EDGE BANDED WITH PERFORATIONS
RUNNING AS CLOSED TO
PERIMETER AS POSSIBLE








#### Planks


TOPPERFO planks allow the ability to design with wood planking in combination with circular perforation. The width of the plank is 192 mm and the joint will be visible. The length can be chosen from standard options below or can be specified as required for the project. All surface finishes are possible with this product option.


Class C Fire Rated			Class A Fire Rated					
Paint 16 mm (0.63")	Wood Veneer 17 mm (0.67")	Melamine 16 mm (0.63")	Paint 16 mm (0.63")	Wood Veneer 17 mm (0.67")	Melamine 16 mm (0.63")			
Standard								
2780 x 192 (109.45" x 7.56")	2780 x 192 (109.45" x 7.56")	2780 x 192 (109.45" x 7.56")	2780 x 192 2780 x 192 (109.45" x 7.56") (109.45" x 7.56		2780 x 192 (109.45" x 7.56")			
-	3640 x 192 (143.3" x 7.56")	-	-	3640 x 192 (143.3" x 7.56")	-			
4080 x 192 (160.63" x 7.56")	-	4080 x 192 (160.63" x 7.56")	4080 x 192 (160.63" x 7.56")	-	4080 x 192 (160.63" x 7.56")			
	custom	lengths are also available	- waste charges may a	pply				

#### Finishing Options











(AT 16MM INCREMENTS) (THROUGH PERFORATIONS)

LONGITUDINAL EDGE\*

\*AVAILABLE UPON REQUEST

6 mm diameter hole 20 mm on center spacing

#### Sound Absorption Values 20/20/6 M 7%



	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1" Insulation 6" Cavity Behind	0.38	0.60	0.61	0.54	0.39	0.30	0.55
1" Insulation Surface Mount	0.20	0.61	0.70	0.55	0.39	0.33	0.55

## Corner Trims and Finishing

